

View Online at <https://aerobasegroup.com/nsn/5945-00-467-1684>

**Overall Length:**

3.906 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.250 inches single mounting facility

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.687 inches single mounting facility

**Overall Height:**

2.976 inches

**Overall Width:**

3.718 inches

**Environmental Protection:**

Dustproof

**Unthreaded Mounting Hole Diameter:**

0.218 inches single mounting facility

**Winding Quantity:**

1

**Coil Quantity:**

1

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

4 unthreaded hole single mounting facility

**Mounting Facility Pattern:**

Rectangular single mounting facility

**Nonpile-up Main Contact Arrangement:**

3 pole, single throw, normally open, momentary action

**Operating Current Rating And Type:**

500.0 milliamperes dc single winding

**Nonpile-up Auxiliary Contact Arrangement:**

1 pole, single throw, normally open, momentary action and 1 pole, double throw, two positions momentary

**Auxiliary Contact Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Operating Voltage Rating And Type At Specificationified Temp:**

28.0 volts dc 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

75.0 amperes ac resistive load and 75.0 amperes dc resistive load

**Main Contact Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Test Data Document:**

81349-mil-r-6106 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

12 pin all functions

**Specification Data:**

96906-ms27714 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A03300

**Mil-std (military Standard):**

Mil-r-6106 spec.