NSN 5945-00-480-5164

Electromagnetic Relay - Page 1 of 2

81349-mil-r-5757/69 government specification



View Online at https://aerobasegroup.com/nsn/5945-00-480-5164

| Overall Length: |
|---|
| 0.375 inches |
| Overall Diameter: |
| 0.335 inches |
| Case Material: |
| Metal |
| Environmental Protection: |
| Hermetic |
| Fragility Factor: |
| Moderately rugged |
| Winding Quantity: |
| 1 |
| Purpose For Which Designed: |
| General |
| Coil Quantity: |
| 1 |
| Winding Dc Resistance Rating: |
| 3.6 kilohms single winding and 4.4 kilohms single winding |
| Duty Type: |
| Continuous |
| Arc Quenching Method: |
| Air |
| Mounting Facility Type And Quantity: |
| 1 terminal single mounting facility |
| Storage Type: |
| General purpose warehouse |
| Nonpile-up Main Contact Arrangement: |
| 1 pole, double throw, one position momentary |
| Time Delay: |
| 0.004 seconds fixed operate time |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 26.0 volts dc 25 degrees celsius single winding |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 100.0 milliamperes dc lamp load |
| Main Contact Maximum Voltage Rating In Volts: |
| 28.0 dc |
| Test Data Document: |
| 81349-mil-r-5757 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Terminal Type And Quantity: |
| 5 wire lead all functions |
| Specification Data: |

NSN 5945-00-480-5164

Electromagnetic Relay - Page 2 of 2



| C | ha | Ιf | 1 | ife | |
|---|-----|----|---|-------|--|
| • | ııe | | _ | .II C | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300