NSN 5945-00-481-3392

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-481-3392

Thread Class:

2a single mounting facility

Thread Direction:

Right-hand single mounting facility

Overall Length:

1.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.305 inches single mounting facility

Overall Height:

0.750 inches

Overall Width:

0.500 inches

Case Material:

Metal

Environmental Protection:

Hermetic

Fragility Factor:

Moderately rugged

Frequency In Hertz:

60.0

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

3 threaded stud single mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

0.375 cubic inches

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.138 inches single mounting facility

Mounting Facility Pattern:

Triangle single mounting facility

NSN 5945-00-481-3392

Electromagnetic Relay - Page 2 of 2



Nonpile-up Main Contact Arrangement:
3 pole, double throw, one position momentary
Time Delay:
0.015 seconds fixed operate and release time
Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:
0.600 inches single mounting facility
Operating Voltage Rating And Type At Specificationified Temp:
115.0 volts ac 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
10.0 amperes ac resistive load and 500.0 milliamperes dc resistive load
Main Contact Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Thread Series Designator:
Unc single mounting facility
Terminal Type And Quantity:
11 wire hook all functions
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A03300