NSN 5945-00-483-3812

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-483-3812

Overall Length:

4.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.812 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.000 inches single mounting facility

Overall Height:

2.563 inches

Overall Width:

2.930 inches

Environmental Protection:

Hermetic

Unthreaded Mounting Hole Diameter:

0.218 inches single mounting facility

Winding Quantity:

1

Coil Quantity:

Winding Dc Resistance Rating:

51.0 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Operating Current Rating And Type:

6.0 milliamperes dc single winding

Time Delay:

0.025 seconds fixed operate and release time

Nonpile-up Auxiliary Contact Arrangement:

2 pole, single throw, normally open, momentary action

Auxiliary Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

50.0 amperes ac resistive load and 50.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

NSN 5945-00-483-3812

Electromagnetic Relay - Page 2 of 2



Ī	erminal	Type	And	Quant	tity:

12 pin all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300