## NSN 5945-00-483-4021

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-483-4021

**Thread Class:** 

2a single mounting facility

**Thread Length:** 

0.344 inches single mounting facility and 0.375 inches single mounting facility

**Overall Length:** 

Between 0.790 inches and 0.800 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:** 

0.402 inches single mounting facility and 0.422 inches single mounting facility

**Overall Height:** 

Between 1.284 inches and 1.335 inches

**Overall Width:** 

Between 0.390 inches and 0.400 inches

**Environmental Protection:** 

Hermetic

**Fragility Factor:** 

Moderately rugged

**Winding Quantity:** 

**Purpose For Which Designed:** 

General

**Coil Quantity:** 

Winding Dc Resistance Rating:

607.5 ohms single winding and 742.5 ohms single winding

**Duty Type:** 

Continuous

**Arc Quenching Method:** 

**Mounting Facility Type And Quantity:** 

2 threaded stud single mounting facility

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

40 single mounting facility

**Thread Size:** 

0.112 inches single mounting facility

**Mounting Facility Pattern:** 

In-line single mounting facility

**Nonpile-up Main Contact Arrangement:** 

2 pole, double throw, one position momentary

Time Delay:

0.005 seconds fixed operate time

## NSN 5945-00-483-4021

Electromagnetic Relay - Page 2 of 2



## Operating Voltage Rating And Type At Specificationified Temp:

14.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

1.0 amperes dc inductive load

**Main Contact Maximum Voltage Rating In Volts:** 

115.0 ac and 28.0 dc

**Thread Series Designator:** 

Unc single mounting facility

**Terminal Type And Quantity:** 

8 wire hook all functions

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A03300