

View Online at <https://aerobasegroup.com/nsn/5945-00-483-6711>

Thread Class:

2a single mounting facility

Thread Direction:

Right-hand single mounting facility

Overall Length:

0.797 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.800 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.220 inches single mounting facility

Overall Height:

1.377 inches

Overall Width:

0.359 inches

Case Material:

Metal

Environmental Protection:

Shock resistant and vibration resistant

Contact Material:

Silver

Winding Quantity:

1

Coil Quantity:

1

Winding Dc Resistance Rating:

10.0 kilohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

2 threaded stud single mounting facility

Cubic Measure:

0.393 cubic inches

Thready Qty Per Inch (tpi):

40 single mounting facility

Thread Size:

0.112 inches single mounting facility

Mounting Facility Pattern:

Diagonal single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Time Delay:

0.007 seconds fixed operate time

Operating Voltage Rating And Type At Specificationified Temp:

96.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac resistive load and 2.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

8 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A03300