NSN 5945-00-484-7655

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-484-7655

Overall	Length:
---------	---------

1.453 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.062 inches single mounting facility

Overall Height:

0.410 inches

Overall Width:

1.376 inches

Environmental Protection:

Hermetic

Unthreaded Mounting Hole Diameter:

0.120 inches single mounting facility

Winding Quantity:

1

Coil Quantity:

1

Winding Dc Resistance Rating:

5.0 kilohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

2 unthreaded hole single mounting facility

Features Provided:

Polarized

Mounting Facility Pattern:

In-line single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Operating Current Rating And Type:

6.0 milliamperes dc single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

300.0 milliamperes ac resistive load and 750.0 milliamperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Test Data Document:

81349-mil-r-5757 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

8 pin all functions

Specification Data:

81349-mil-r-5757/13 government specification

Shelf Life:

N/a

NSN 5945-00-484-7655

Electromagnetic Relay - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A03300