NSN 5945-00-485-4926

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-485-4926

Thread Class: 2a single mounting facility **Thread Direction:** Right-hand single mounting facility **Overall Length:** 1.531 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 1.187 inches single mounting facility Center To Center Distance Between Mounting Facilities Parallel To Width: 1.187 inches single mounting facility **Overall Height:** 2.624 inches **Overall Width:** 1.531 inches **Case Material:** Metal **Environmental Protection:** Hermetic **Fragility Factor:** Moderately rugged Winding Quantity: 1 **Purpose For Which Designed:** General **Coil Quantity:** 1 **Duty Type:** Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 4 threaded stud single mounting facility Storage Type: General purpose warehouse **Cubic Measure:** 6.150 cubic inches Thready Qty Per Inch (tpi): 32 single mounting facility **Thread Size:** 0.138 inches single mounting facility

Mounting Facility Pattern:

Rectangular single mounting facility

NSN 5945-00-485-4926

Electromagnetic Relay - Page 2 of 2



Nonpile-up Main Contact Arrangement: 6 pole, double throw, one position momentary **Operating Current Rating And Type:** 180.0 milliamperes dc single winding **Time Delay:** 0.02 seconds fixed operate and release time **Operating Voltage Rating And Type At Specificationified Temp:** 28.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 1.5 amperes ac motor load and 1.5 amperes dc motor load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc **Test Data Document:** 81349-mil-r-6106 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Thread Series Designator:** Unc single mounting facility **Terminal Type And Quantity:** 20 wire lead all functions **Specification Data:** 96906-ms25270 government standard Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A03300 Mil-std (military Standard): Mil-r-6106 spec.