NSN 5945-00-487-3322

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-487-3322
Thread Class:
2a single mounting facility
Thread Length:
0.380 inches single mounting facility
Overall Length:
1.300 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.746 inches single mounting facility and 0.754 inches single mounting facility
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.558 inches single mounting facility and 0.566 inches single mounting facility
Overall Height:
0.375 inches
Overall Width:
1.075 inches
Environmental Protection:
Hermetic
Fragility Factor:
Moderately rugged
Frequency In Hertz:
400.0
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
2 threaded stud single mounting facility
Storage Type:
General purpose warehouse
Features Provided:
Coil voltage suppression
Thready Qty Per Inch (tpi):
32 single mounting facility
Thread Size:
0.138 inches single mounting facility

Mounting Facility Pattern:

Diagonal single mounting facility

NSN 5945-00-487-3322

Electromagnetic Relay - Page 2 of 2



Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Time Delay:

0.02 seconds fixed operate and release time

Operating Voltage Rating And Type At Specificationified Temp:

115.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

5.0 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

8 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300