

View Online at <https://aerobasegroup.com/nsn/5945-00-489-2073>

Overall Length:

3.704 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.187 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.187 inches single mounting facility

Overall Height:

3.200 inches

Overall Width:

3.000 inches

Case Material:

Metal

Environmental Protection:

Hermetic

Unthreaded Mounting Hole Diameter:

0.173 inches single mounting facility

Fragility Factor:

Moderately rugged

Winding Quantity:

2

Purpose For Which Designed:

General

Coil Quantity:

2

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

Storage Type:

General purpose warehouse

Features Provided:

Latching contacts and polarized

Cubic Measure:

35.558 cubic inches

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

3 pole, single throw, normally open, momentary action

Operating Current Rating And Type:

250.0 milliamperes dc single winding

Time Delay:

0.02 seconds fixed operate time

Operating Voltage Rating And Type At Specificationified Temp:

25.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

20.0 amperes ac motor load and 20.0 amperes dc motor load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Test Data Document:

81349-mil-r-6106 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

10 screw all functions

Specification Data:

96906-ms27706 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A03300

Mil-std (military Standard):

Mil-r-6106 spec.