## NSN 5945-00-492-1974

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-492-1974 **Overall Length:** 0.610 inches **Overall Height:** 0.310 inches Overall Width: 0.430 inches **Environmental Protection:** Hermetic **Fragility Factor:** Moderately rugged Winding Quantity: **Purpose For Which Designed:** General **Coil Quantity:** Winding Dc Resistance Rating: 1.35 kilohms single winding **Duty Type:** Continuous **Mounting Facility Type And Quantity:** 1 plug-in terminal single mounting facility Storage Type: General purpose warehouse **Nonpile-up Main Contact Arrangement:** 2 pole, double throw, one position momentary Operating Voltage Rating And Type At Specificationified Temp: 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 125.0 milliamperes ac resistive load and 1.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 26.5 dc **Test Data Document:** 81349-mil-r-5757 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 8 pin all functions

Shelf Life: N/a

**Unit Of Measure:** 

**Specification Data:** 

81349-mil-r-5757/37 government specification

## NSN 5945-00-492-1974

Electromagnetic Relay - Page 2 of 2



Demilitarization:

No

Fiig:

A03300