NSN 5945-00-494-4876

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-494-4876

Overall Length:

0.280 inches

Overall Diameter:

0.335 inches

Case Material:

Metal

Environmental Protection:

Hermetic

Fragility Factor:

Moderately rugged

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Winding Dc Resistance Rating:

1.017 kilohms single winding and 1.243 kilohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

1 terminal single mounting facility

Storage Type:

General purpose warehouse

Nonpile-up Main Contact Arrangement:

1 pole, double throw, one position momentary

Time Delay:

0.002 seconds fixed operate and release time

Operating Voltage Rating And Type At Specificationified Temp:

18.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

100.0 milliamperes dc lamp load

Main Contact Maximum Voltage Rating In Volts:

28.0 dc

Test Data Document:

81349-mil-r-5757 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

5 wire lead all functions

Specification Data:

81349-mil-r-5757/38 government specification

Shelf Life:

N/a

NSN 5945-00-494-4876

Electromagnetic Relay - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A03300

