NSN 5945-00-497-0117

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-497-0117

Thread Class: 2a single mounting facility **Thread Direction:** Right-hand single mounting facility **Overall Length:** 1.531 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 1.187 inches single mounting facility **Center To Center Distance Between Mounting Facilities Parallel To Width:** 0.687 inches single mounting facility **Overall Height:** 2.218 inches **Overall Width:** 1.100 inches **Environmental Protection:** Hermetic and salt spray resistant and shock resistant and vibration resistant and water resistant **Contact Material:** Silver **Contact Surface Treatment:** Gold Frequency In Hertz: 60.0 Winding Quantity: **Coil Quantity: Duty Type:** Continuous **Mounting Facility Type And Quantity:** 4 threaded stud single mounting facility Thready Qty Per Inch (tpi): 32 single mounting facility **Thread Size:** 0.138 inches single mounting facility **Mounting Facility Pattern:** Rectangular single mounting facility **Nonpile-up Main Contact Arrangement:** 2 pole, double throw, one position momentary

Time Delay:

0.05 seconds fixed release time

Operating Voltage Rating And Type At Specificationified Temp:

115.0 volts ac 25 degrees celsius single winding

NSN 5945-00-497-0117

Electromagnetic Relay - Page 2 of 2



Main	Contact	Load	Current	Rating	At	Maximum	Rated	Voltage:

10.0 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac

Precious Material And Location:

Contacts silver and contact surfaces gold

Precious Material:

Silver and gold

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

8 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300