NSN 5945-00-497-0119

Electromagnetic Relay - Page 1 of 2

Thread Class:

Shelf Life:

N/a

Thread Direction:

2a single mounting facility

Right-hand single mounting facility



View Online at https://aerobasegroup.com/nsn/5945-00-497-0119

Center To Center Distance Between Mounting Facilities Parallel To Length:

| 1.562 inches single mounting facility |
|---|
| Overall Height: |
| 2.437 inches |
| Case Material: |
| Metal |
| Environmental Protection: |
| Hermetic and salt spray resistant and shock resistant and vibration resistant and water resistant |
| Frequency In Hertz: |
| 400.0 |
| Winding Quantity: |
| 1 |
| Coil Quantity: |
| 1 |
| Duty Type: |
| Continuous |
| Mounting Facility Type And Quantity: |
| 2 threaded stud single mounting facility |
| Thready Qty Per Inch (tpi): |
| 32 single mounting facility |
| Thread Size: |
| 0.138 inches single mounting facility |
| Mounting Facility Pattern: |
| In-line single mounting facility |
| Nonpile-up Main Contact Arrangement: |
| 4 pole, double throw, one position momentary |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 115.0 volts ac 25 degrees celsius single winding |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 1.0 amperes ac resistive load and 2.0 amperes dc resistive load |
| Main Contact Maximum Voltage Rating In Volts: |
| 115.0 ac and 26.5 dc |
| Thread Series Designator: |
| Unc single mounting facility |
| Terminal Type And Quantity: |
| 14 wire hook all functions |

NSN 5945-00-497-0119

Electromagnetic Relay - Page 2 of 2



| ш | ın | 10 | <i>(</i>)+ | Measure: | |
|---|----|----|-------------|----------|--|
| | | | | | |

--

Demilitarization:

No

Fiig:

A03300