

View Online at <https://aerobasegroup.com/nsn/5945-00-497-0247>

Overall Length:

3.125 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.750 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.750 inches single mounting facility

Overall Height:

3.250 inches

Overall Width:

1.031 inches

Environmental Protection:

Dust tight

Unthreaded Mounting Hole Diameter:

0.144 inches single mounting facility

Contact Material:

Rhodium and silver

Contact Surface Treatment:

Gold flash

Winding Quantity:

1

Coil Quantity:

1

Winding Dc Resistance Rating:

150.0 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

Pile-up Main Contact Form Arrangement:

36c

Mounting Facility Pattern:

Rectangular single mounting facility

Operating Current Rating And Type:

187.0 milliamperes dc single winding

Time Delay:

0.03 seconds fixed operate time

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

5.0 amperes ac resistive load and 5.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Precious Material:

Gold and rhodium and silver

Terminal Type And Quantity:

110 tab, solder lug all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300