NSN 5945-00-497-4503

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-497-4503

view Online at https://acrobasegroup.com/nsh/os+5-00-45/-4505
Thread Class:
2a single mounting facility
Overall Length:
1.906 inches
Overall Height:
1.250 inches
Overall Width:
1.437 inches
Environmental Protection:
Hermetic
Winding Quantity:
1
Coil Quantity:
1
Winding Dc Resistance Rating:
188.0 ohms single winding
Duty Type:
Continuous
Mounting Facility Type And Quantity:
3 threaded stud single mounting facility
Thread Size:
0.112 inches single mounting facility
Mounting Facility Pattern:
Triangle single mounting facility
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary
Operating Current Rating And Type:
150.0 milliamperes dc single winding
Time Delay:
0.50 seconds adjustable operate time and 5.00 seconds adjustable operate time
Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:
0.625 inches single mounting facility
Operating Voltage Rating And Type At Specificationified Temp:
28.0 volts dc 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
2.0 amperes dc resistive load
Main Contact Maximum Voltage Rating In Volts:
30.0 dc
Thread Series Designator:
Unc single mounting facility
Terminal Type And Quantity:

8 pin all functions

NSN 5945-00-497-4503

Electromagnetic Relay - Page 2 of 2



		ife:	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300