## NSN 5945-00-500-7881

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-500-7881

| view Offline at https://defobasegroup.com/nsi//0345-00-300-7001  |
|--|
| Thread Class:  |
| 2a single mounting facility  |
| Overall Length:  |
| 1.340 inches   |
| Center To Center Distance Between Mounting Facilities Parallel To Width:                                 |
| 0.500 inches single mounting facility  |
| Overall Height:  |
| 1.969 inches   |
| Overall Width:   |
| 0.970 inches   |
| Environmental Protection:  |
| Hermetic   |
| Winding Quantity:  |
| 1  |
| Coil Quantity:   |
| 1  |
| Winding Dc Resistance Rating:  |
| 280.0 ohms single winding  |
| Duty Type:   |
| Continuous   |
| Mounting Facility Type And Quantity:   |
| 3 threaded stud single mounting facility   |
| Thready Qty Per Inch (tpi):  |
| 40 single mounting facility  |
| Thread Size:   |
| 0.112 inches single mounting facility  |
| Mounting Facility Pattern:   |
| Triangle single mounting facility  |
| Nonpile-up Main Contact Arrangement:   |
| 2 pole, single throw, normally open, momentary action  |
| Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: |
| 1.000 inches single mounting facility  |
| Operating Voltage Rating And Type At Specificationified Temp:  |
| 27.5 volts dc 25 degrees celsius single winding  |
| Main Contact Load Current Rating At Maximum Rated Voltage:   |
| 5.0 amperes dc resistive load  |
| Main Contact Maximum Voltage Rating In Volts:  |
| 27.5 dc  |
| Special Features:  |
| The 2 form a contact arrangements are series connected internally  |

Thread Series Designator:

Unc single mounting facility

## NSN 5945-00-500-7881

Electromagnetic Relay - Page 2 of 2



| Terminal T | ype And | Quantity: |
|------------|---------|-----------|
|------------|---------|-----------|

6 wire hook all functions

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300