NSN 5945-00-502-3064



Electrical Solenoid - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5945-00-502-3064 **Body Style:** Open frame **Center To Center Distance Between Mounting Facilities Parallel To Length:** 3.812 inches **Center To Center Distance Between Mounting Facilities Parallel To Width:** 2.625 inches **Body Length:** 3.125 inches **Body Width:** 2.250 inches **Body Height:** 4.687 inches **Case Material:** Aluminum **Case Surface Treatment:** Zinc or cadmium **Environmental Protection:** Fungus proof **Unthreaded Mounting Hole Diameter:** Between 0.252 inches and 0.255 inches **Actuator Width:** 0.726 inches Frequency In Hertz: 60.0 **Inclosure Type:** Uninclosed **Magnetic Coil Quantity: Electrical Resistance:** 78.50 ohms **Duty Type:** Continuous **Terminal Location:** Circumference **Voltage Rating In Volts:** 110.0 ac **Mounting Facility Type And Quantity:** 6 unthreaded hole **Current Rating:**

1.4 amperesActuator Stroke Type:Push

NSN 5945-00-502-3064 Electrical Solenoid - Page 2 of 2



Linear Force Delivered:
19.50 pounds
Power Takeoff Connection Type:
Plain-drilled
Energizing Stroke Maximum Length:
0.625 inches
Mounting Facility Pattern:
Six position rectangular
Special Features:
Surface treatment document and classification: baqq-z-325, type 2, class 2 or baqq-p-416, type 2, class 2
Surface Treatment Specification:
Qq-z-325, type 2, class 2 federal specification single treatment response or qq-p-416, type 2, class 2 federal specification single treatment
response
Terminal Type And Quantity:
2 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A134a0