NSN 5945-00-502-5084

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-502-5084

Overall Length:

4.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.688 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.438 inches single mounting facility

Overall Height:

2.870 inches

Overall Width:

3.000 inches

Unthreaded Mounting Hole Diameter:

0.177 inches single mounting facility

End Application:

Mk 33

Frequency In Hertz:

60.0

Winding Quantity:

Coil Quantity:

Winding Dc Resistance Rating:

180.0 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, single throw, normally open, momentary action

Operating Current Rating And Type:

140.0 milliamperes ac single winding

Operating Voltage Rating And Type At Specificationified Temp:

115.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

30.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

230.0 dc

Special Features:

Arc quenching method: blowout coil

Terminal Type And Quantity:

6 pin all functions

NSN 5945-00-502-5084

Electromagnetic Relay - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300