

View Online at <https://aerobasegroup.com/nsn/5945-00-503-6262>

Thread Class:

2a first mounting facility

Overall Length:

3.938 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.688 inches first mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.688 inches first mounting facility

Overall Height:

4.500 inches

Overall Width:

2.750 inches

Environmental Protection:

Humidity proof and dustproof and corrosion resistant and fungus resistant

Winding Quantity:

2

Coil Quantity:

1

Winding Dc Resistance Rating:

80.8 ohms all windings

Duty Type:

Intermittent

Mounting Facility Type And Quantity:

4 threaded stud first mounting facility

Thread Size:

0.250 inches first mounting facility

Mounting Facility Pattern:

Rectangular first mounting facility

Operating Current Rating And Type:

350.0 milliamperes dc all windings

Time Delay:

0.100 seconds fixed release time and 0.650 seconds fixed release time

Operating Voltage Rating And Type At Specificationified Temp:

24.0 volts dc 25 degrees celsius all windings

Main Contact Load Current Rating At Maximum Rated Voltage:

35.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

30.0 dc

Special Features:

2 studs no. 8-32 nc2 spaced 3.375 in. C to c; studs 1/2 in. Lg

Thread Series Designator:

Unf first mounting facility

Specification Or Standard:

B class and 2 grade

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300