

View Online at <https://aerobasegroup.com/nsn/5945-00-503-6262>

**Thread Class:**

2a first mounting facility

**Overall Length:**

3.938 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.688 inches first mounting facility

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.688 inches first mounting facility

**Overall Height:**

4.500 inches

**Overall Width:**

2.750 inches

**Environmental Protection:**

Humidity proof and dustproof and corrosion resistant and fungus resistant

**Winding Quantity:**

2

**Coil Quantity:**

1

**Winding Dc Resistance Rating:**

80.8 ohms all windings

**Duty Type:**

Intermittent

**Mounting Facility Type And Quantity:**

4 threaded stud first mounting facility

**Thread Size:**

0.250 inches first mounting facility

**Mounting Facility Pattern:**

Rectangular first mounting facility

**Operating Current Rating And Type:**

350.0 milliamperes dc all windings

**Time Delay:**

0.100 seconds fixed release time and 0.650 seconds fixed release time

**Operating Voltage Rating And Type At Specificationified Temp:**

24.0 volts dc 25 degrees celsius all windings

**Main Contact Load Current Rating At Maximum Rated Voltage:**

35.0 amperes dc resistive load

**Main Contact Maximum Voltage Rating In Volts:**

30.0 dc

**Special Features:**

2 studs no. 8-32 nc2 spaced 3.375 in. C to c; studs 1/2 in. Lg

**Thread Series Designator:**

Unf first mounting facility

**Specification Or Standard:**

B class and 2 grade

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A03300