NSN 5945-00-504-5358

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-504-5358

Thread Class: 2b second mounting facility **Thread Direction:** Right-hand second mounting facility **Overall Length:** 3.250 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 1.750 inches second mounting facility **Overall Height:** 4.520 inches **Overall Width:** 3.090 inches **Case Material: Plastic Environmental Protection:** Dustproof **Unthreaded Mounting Hole Diameter:** 0.199 inches first mounting facility Center To Center Distance Between Mounting Facilities Parallel To Height: 0.500 inches second mounting facility **Fragility Factor:** Moderately rugged Frequency In Hertz: 60.0 Winding Quantity: **Purpose For Which Designed:** General **Coil Quantity: Duty Type:** Continuous **Arc Quenching Method:** Air **Mounting Facility Type And Quantity:** 6 unthreaded hole first mounting facility Storage Type:

Cubic Measure: 45.392 cubic inches Thready Qty Per Inch (tpi): 32 second mounting facility

General purpose warehouse

NSN 5945-00-504-5358

Electromagnetic Relay - Page 2 of 2



Th	read	Size:
	ıcau	UIZE.

0.164 inches second mounting facility

Mounting Facility Pattern:

Rectangular second mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Time Delay:

1.00 minutes adjustable operate time and 10.00 minutes adjustable operate time

Nonpile-up Auxiliary Contact Arrangement:

2 pole, double throw, one position momentary

Auxiliary Contact Maximum Voltage Rating In Volts:

480.0 ac

Operating Voltage Rating And Type At Specificationified Temp:

110.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

10.0 amperes ac resistive load and 15.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

240.0 ac and 30.0 dc

Auxiliary Contact Load Current Rating At Maximum Rated Voltage:

10.0 amperes ac resistive load

Energizing Element Power Rating:

8.0 watts

Thread Series Designator:

Unc second mounting facility

Terminal Type And Quantity:

14 screw all functions

Shelf Life:

N/a

Unit Of Measure:

_

Demilitarization:

No

Fiig:

A03300