

View Online at <https://aerobasegroup.com/nsn/5945-00-508-1808>

**Overall Length:**

3.200 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.730 inches single mounting facility

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.000 inches single mounting facility

**Overall Height:**

3.780 inches

**Overall Width:**

3.210 inches

**Environmental Protection:**

Shock proof and vibration proof

**Unthreaded Mounting Hole Diameter:**

0.182 inches single mounting facility and 0.197 inches single mounting facility

**Winding Quantity:**

1

**Coil Quantity:**

1

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

4 unthreaded hole single mounting facility

**Features Provided:**

Coil voltage suppression and polarized

**Mounting Facility Pattern:**

Rectangular single mounting facility

**Nonpile-up Main Contact Arrangement:**

3 pole, double throw, one position momentary

**Time Delay:**

0.02 seconds fixed operate time

**Nonpile-up Auxiliary Contact Arrangement:**

2 pole, double throw, one position momentary and 1 pole, single throw, normally open, momentary action

**Auxiliary Contact Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Operating Voltage Rating And Type At Specificationified Temp:**

28.0 volts dc 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

25.0 amperes ac resistive load

**Main Contact Maximum Voltage Rating In Volts:**

200.0 ac

**Auxiliary Contact Load Current Rating At Maximum Rated Voltage:**

5.0 amperes ac resistive load and 5.0 amperes dc resistive load

**Terminal Type And Quantity:**

19 threaded stud all functions

**Fsc Application Data (non-core):**

Electrical system, aircraft

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A03300