

View Online at <https://aerobasegroup.com/nsn/5945-00-508-1808>

Overall Length:

3.200 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.730 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.000 inches single mounting facility

Overall Height:

3.780 inches

Overall Width:

3.210 inches

Environmental Protection:

Shock proof and vibration proof

Unthreaded Mounting Hole Diameter:

0.182 inches single mounting facility and 0.197 inches single mounting facility

Winding Quantity:

1

Coil Quantity:

1

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

Features Provided:

Coil voltage suppression and polarized

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

3 pole, double throw, one position momentary

Time Delay:

0.02 seconds fixed operate time

Nonpile-up Auxiliary Contact Arrangement:

2 pole, double throw, one position momentary and 1 pole, single throw, normally open, momentary action

Auxiliary Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

25.0 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

200.0 ac

Auxiliary Contact Load Current Rating At Maximum Rated Voltage:

5.0 amperes ac resistive load and 5.0 amperes dc resistive load

Terminal Type And Quantity:

19 threaded stud all functions

Fsc Application Data (non-core):

Electrical system, aircraft

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300