## NSN 5945-00-518-7886

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-518-7886

| 2s single mounting facility  Overall Length: 2.500 inches  Overall Height: 1.400 inches  Overall Width: 1.620 inches  Environmental Protection: Hermetic  Winding Quantity: 1  Coil Quantity: 1  Winding Dc Resistance Rating: 390.0 ohms single winding  Duty Type: Continuous  Mounting Facility Type And Quantity: 3 threaded stud single mounting facility  Pile-up Main Contact Form Arrangement: 1a  Thready Qty Per Inch (tpi): 32 single mounting facility  Thread Size: 0.138 inches single mounting facility  Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: 1.062 inches single mounting facility  Operating Voltage Rating And Type At Specificationified Temp: 27.0 volts de 25 degrees celsius single winding  Main Contact Maximum Voltage Rating In Volts: 115.0 ac  Thread Series Designator:  |  |
|---|--|
| Coverall Length:  2.500 inches  Overall Height:  1.400 inches  Overall Width:  1.620 inches  Environmental Protection:  Hermetic  Winding Quantity:  1  Coil Quantity:  1  Winding Dc Resistance Rating:  390.0 ohms single winding  Duty Type:  Continuous  Mounting Facility Type And Quantity:  1 threaded stud single mounting facility  Pile-up Main Contact Form Arrangement:  1a  Thready Qty Per Inch (tpi):  32 single mounting facility  Thread Size:  0.138 inches single mounting facility  Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:  1.062 inches single mounting facility  Operating Voltage Rating And Type At Specificationified Temp:  27.0 volts de 25 degrees celsius single winding  Main Contact Load Current Rating At Maximum Rated Voltage:  1.05 ac  Thread Scries Designator:   | Thread Class:  |
| 2.500 inches Overall Height: 1.400 inches Overall Width: 1.620 inches Environmental Protection: Hermetic Winding Quantity: 1 Coil Quantity: 1 Winding Dc Resistance Rating: 390.0 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 3 threaded stud single mounting facility Pile-up Main Contact Form Arrangement: 1a Thready Qty Per Inch (tpl): 32 single mounting facility Pilese mounting facility Mounting Facility Pattern: Triangle single mounting facility  Mounting Facility Pattern: Triangle single mounting facility  Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: 1.062 inches single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 27.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes ac resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac Thread Series Designator: |  |
| Overall Height:  1.400 inches Overall Width:  1.620 inches Environmental Protection: Hermetic Winding Quantity:  1 Coil Quantity:  1 Winding Dc Resistance Rating: 390.0 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 3 threaded stud single mounting facility Pile-up Main Contact Form Arrangement: 1a Thready Qty Per Inch (tpi): 32 single mounting facility Thread Size: 0.138 inches single mounting facility Mounting Facility Pattern: Triangle single mounting facility Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: 1.062 inches single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 27.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes ac resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac Thread Series Designator:   | -  |
| 1.400 inches Overall Width: 1.620 inches Environmental Protection: Hermetic Winding Quantity: 1 Coil Quantity: 1 Winding Dc Resistance Rating: 390.0 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 3 threaded stud single mounting facility Pile-up Main Contact Form Arrangement: 1a Thready Qty Per Inch (tpi): 32 single mounting facility Thread Size: 0.138 inches single mounting facility Mounting Facility Pattern: Triangle single mounting facility Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: 1.062 inches single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 27.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes ac resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac Thread Series Designator:   | 2.500 inches   |
| Overall Width:  1.620 inches  Environmental Protection: Hermetic  Winding Quantity:  1  Coil Quantity:  1  Winding Dc Resistance Rating: 390.0 ohms single winding  Duty Type: Continuous  Mounting Facility Type And Quantity: 3 threaded stud single mounting facility Pile-up Main Contact Form Arrangement: 1a  Thready Qty Per Inch (tpi): 32 single mounting facility Thread Size: 0.138 inches single mounting facility Mounting Facility Pattern: Triangle single mounting facility Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: 1.062 inches single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 27.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes ac resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac Thread Series Designator:  | Overall Height:  |
| 1.620 inches Environmental Protection: Hermetic Winding Quantity: 1 Coil Quantity: 1 Winding Dc Resistance Rating: 390.0 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 3 threaded stud single mounting facility Pile-up Main Contact Form Arrangement: 1a Thready Qty Per Inch (tpi): 32 single mounting facility Thread Size: 0.138 inches single mounting facility Mounting Facility Type Attern: Triangle single mounting facility Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: 1.062 inches single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 27.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes ac resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac Thread Series Designator:   | 1.400 inches   |
| Environmental Protection: Hermetic  Winding Quantity:  1 Coil Quantity: 1 Winding Dc Resistance Rating: 390.0 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 3 threaded stud single mounting facility Pile-up Main Contact Form Arrangement: 1a Thready Qty Per Inch (tpi): 32 single mounting facility Thread Size: 0.138 inches single mounting facility Mounting Facility Pattern: Triangle single mounting facility Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: 1.062 inches single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 27.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes ac resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac Thread Series Designator:  | Overall Width:   |
| Hermettic  Winding Quantity: 1  Coil Quantity: 1  Winding Dc Resistance Rating: 390.0 ohms single winding  Duty Type: Continuous  Mounting Facility Type And Quantity: 3 threaded stud single mounting facility  Pile-up Main Contact Form Arrangement: 1a  Thready Qty Per Inch (tpl): 32 single mounting facility  Thread Size: 0.138 inches single mounting facility  Mounting Facility Pattern: Triangle single mounting facility  Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: 1.062 inches single mounting facility  Operating Voltage Rating And Type At Specificationified Temp: 27.0 volts dc 25 degrees celsius single winding  Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes ac resistive load  Main Contact Maximum Voltage Rating In Volts: 115.0 ac Thread Series Designator:  | 1.620 inches   |
| Winding Quantity:  1 Coil Quantity:  1 Winding Dc Resistance Rating: 390.0 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 3 threaded stud single mounting facility Pile-up Main Contact Form Arrangement: 1a Thready Qty Per Inch (tpi): 32 single mounting facility Thread Size: 0.138 inches single mounting facility Mounting Facility Pattern: Triangle single mounting facility Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: 1.062 inches single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 27.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes ac resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac Thread Series Designator:   | Environmental Protection:  |
| Coil Quantity:  1 Winding Dc Resistance Rating: 390.0 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 3 threaded stud single mounting facility Pile-up Main Contact Form Arrangement: 1a Thready Qty Per Inch (tpi): 32 single mounting facility Thread Size: 0.138 inches single mounting facility Mounting Facility Pattern: Triangle single mounting facility Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: 1.062 inches single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 27.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes ac resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac Thread Series Designator:  | Hermetic   |
| Coil Quantity:  1 Winding Dc Resistance Rating: 390.0 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 3 threaded stud single mounting facility Pile-up Main Contact Form Arrangement: 1a Thready Qty Per Inch (tpi): 32 single mounting facility Thread Size: 0.138 inches single mounting facility Mounting Facility Pattern: Triangle single mounting facility Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: 1.062 inches single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 27.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes ac resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac Thread Series Designator:  | Winding Quantity:  |
| Winding Dc Resistance Rating: 390.0 ohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 3 threaded stud single mounting facility Pile-up Main Contact Form Arrangement: 1a Thready Qty Per Inch (tpi): 32 single mounting facility Thread Size: 0.138 inches single mounting facility Mounting Facility Pattern: Triangle single mounting facility Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: 1.062 inches single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 27.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes ac resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac Thread Series Designator:  | 1  |
| Winding Dc Resistance Rating:  390.0 ohms single winding  Duty Type: Continuous  Mounting Facility Type And Quantity: 3 threaded stud single mounting facility Pile-up Main Contact Form Arrangement: 1a  Thready Qty Per Inch (tpi): 32 single mounting facility Thread Size: 0.138 inches single mounting facility  Mounting Facility Pattern: Triangle single mounting facility  Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: 1.062 inches single mounting facility  Operating Voltage Rating And Type At Specificationified Temp: 27.0 volts dc 25 degrees celsius single winding  Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes ac resistive load  Main Contact Maximum Voltage Rating In Volts: 115.0 ac  Thread Series Designator:  | Coil Quantity:   |
| 390.0 ohms single winding  Duty Type: Continuous  Mounting Facility Type And Quantity: 3 threaded stud single mounting facility  Pile-up Main Contact Form Arrangement: 1a  Thready Qty Per Inch (tpi): 32 single mounting facility  Thread Size: 0.138 inches single mounting facility  Mounting Facility Pattern: Triangle single mounting facility  Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: 1.062 inches single mounting facility  Operating Voltage Rating And Type At Specificationified Temp: 27.0 volts dc 25 degrees celsius single winding  Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes ac resistive load  Main Contact Maximum Voltage Rating In Volts: 115.0 ac  Thread Series Designator:   | 1  |
| Duty Type: Continuous  Mounting Facility Type And Quantity: 3 threaded stud single mounting facility Pile-up Main Contact Form Arrangement: 1a Thready Qty Per Inch (tpi): 32 single mounting facility Thread Size: 0.138 inches single mounting facility Mounting Facility Pattern: Triangle single mounting facility Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: 1.062 inches single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 27.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes ac resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac Thread Series Designator:   | Winding Dc Resistance Rating:  |
| Mounting Facility Type And Quantity:  3 threaded stud single mounting facility  Pile-up Main Contact Form Arrangement:  1a  Thready Qty Per Inch (tpi):  32 single mounting facility  Thread Size:  0.138 inches single mounting facility  Mounting Facility Pattern:  Triangle single mounting facility  Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:  1.062 inches single mounting facility  Operating Voltage Rating And Type At Specificationified Temp:  27.0 volts dc 25 degrees celsius single winding  Main Contact Load Current Rating At Maximum Rated Voltage:  1.0 amperes ac resistive load  Main Contact Maximum Voltage Rating In Volts:  115.0 ac  Thread Series Designator:  | 390.0 ohms single winding  |
| Mounting Facility Type And Quantity: 3 threaded stud single mounting facility Pile-up Main Contact Form Arrangement: 1a Thready Qty Per Inch (tpi): 32 single mounting facility Thread Size: 0.138 inches single mounting facility Mounting Facility Pattern: Triangle single mounting facility Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: 1.062 inches single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 27.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes ac resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac Thread Series Designator:  | Duty Type:   |
| 3 threaded stud single mounting facility Pile-up Main Contact Form Arrangement:  1a Thready Qty Per Inch (tpi): 32 single mounting facility Thread Size: 0.138 inches single mounting facility Mounting Facility Pattern: Triangle single mounting facility Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: 1.062 inches single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 27.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes ac resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac Thread Series Designator:  | Continuous   |
| Pile-up Main Contact Form Arrangement:  1a  Thready Qty Per Inch (tpi): 32 single mounting facility  Thread Size: 0.138 inches single mounting facility  Mounting Facility Pattern: Triangle single mounting facility  Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: 1.062 inches single mounting facility  Operating Voltage Rating And Type At Specificationified Temp: 27.0 volts dc 25 degrees celsius single winding  Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes ac resistive load  Main Contact Maximum Voltage Rating In Volts: 115.0 ac  Thread Series Designator:   | Mounting Facility Type And Quantity:   |
| Thready Qty Per Inch (tpi): 32 single mounting facility Thread Size: 0.138 inches single mounting facility Mounting Facility Pattern: Triangle single mounting facility Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: 1.062 inches single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 27.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes ac resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac Thread Series Designator:  | 3 threaded stud single mounting facility   |
| Thready Qty Per Inch (tpi): 32 single mounting facility Thread Size: 0.138 inches single mounting facility Mounting Facility Pattern: Triangle single mounting facility Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: 1.062 inches single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 27.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes ac resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac Thread Series Designator:  | Pile-up Main Contact Form Arrangement:   |
| Thread Size:  0.138 inches single mounting facility  Mounting Facility Pattern:  Triangle single mounting facility  Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:  1.062 inches single mounting facility  Operating Voltage Rating And Type At Specificationified Temp:  27.0 volts dc 25 degrees celsius single winding  Main Contact Load Current Rating At Maximum Rated Voltage:  1.0 amperes ac resistive load  Main Contact Maximum Voltage Rating In Volts:  115.0 ac  Thread Series Designator:  | 1a   |
| Thread Size:  0.138 inches single mounting facility  Mounting Facility Pattern:  Triangle single mounting facility  Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:  1.062 inches single mounting facility  Operating Voltage Rating And Type At Specificationified Temp:  27.0 volts dc 25 degrees celsius single winding  Main Contact Load Current Rating At Maximum Rated Voltage:  1.0 amperes ac resistive load  Main Contact Maximum Voltage Rating In Volts:  115.0 ac  Thread Series Designator:  | Thready Qty Per Inch (tpi):  |
| 0.138 inches single mounting facility  Mounting Facility Pattern:  Triangle single mounting facility  Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:  1.062 inches single mounting facility  Operating Voltage Rating And Type At Specificationified Temp:  27.0 volts dc 25 degrees celsius single winding  Main Contact Load Current Rating At Maximum Rated Voltage:  1.0 amperes ac resistive load  Main Contact Maximum Voltage Rating In Volts:  115.0 ac  Thread Series Designator:  | 32 single mounting facility  |
| Mounting Facility Pattern: Triangle single mounting facility Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: 1.062 inches single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 27.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes ac resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac Thread Series Designator:   | Thread Size:   |
| Triangle single mounting facility  Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:  1.062 inches single mounting facility  Operating Voltage Rating And Type At Specificationified Temp:  27.0 volts dc 25 degrees celsius single winding  Main Contact Load Current Rating At Maximum Rated Voltage:  1.0 amperes ac resistive load  Main Contact Maximum Voltage Rating In Volts:  115.0 ac  Thread Series Designator:   | 0.138 inches single mounting facility  |
| Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:  1.062 inches single mounting facility  Operating Voltage Rating And Type At Specificationified Temp:  27.0 volts dc 25 degrees celsius single winding  Main Contact Load Current Rating At Maximum Rated Voltage:  1.0 amperes ac resistive load  Main Contact Maximum Voltage Rating In Volts:  115.0 ac  Thread Series Designator:  | Mounting Facility Pattern:   |
| 1.062 inches single mounting facility  Operating Voltage Rating And Type At Specificationified Temp:  27.0 volts dc 25 degrees celsius single winding  Main Contact Load Current Rating At Maximum Rated Voltage:  1.0 amperes ac resistive load  Main Contact Maximum Voltage Rating In Volts:  115.0 ac  Thread Series Designator:  | Triangle single mounting facility  |
| Operating Voltage Rating And Type At Specificationified Temp:  27.0 volts dc 25 degrees celsius single winding  Main Contact Load Current Rating At Maximum Rated Voltage:  1.0 amperes ac resistive load  Main Contact Maximum Voltage Rating In Volts:  115.0 ac  Thread Series Designator:   | Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: |
| 27.0 volts dc 25 degrees celsius single winding  Main Contact Load Current Rating At Maximum Rated Voltage:  1.0 amperes ac resistive load  Main Contact Maximum Voltage Rating In Volts:  115.0 ac  Thread Series Designator:  | 1.062 inches single mounting facility  |
| Main Contact Load Current Rating At Maximum Rated Voltage:  1.0 amperes ac resistive load  Main Contact Maximum Voltage Rating In Volts:  115.0 ac  Thread Series Designator:   | Operating Voltage Rating And Type At Specificationified Temp:  |
| Main Contact Load Current Rating At Maximum Rated Voltage:  1.0 amperes ac resistive load  Main Contact Maximum Voltage Rating In Volts:  115.0 ac  Thread Series Designator:   | 27.0 volts dc 25 degrees celsius single winding  |
| Main Contact Maximum Voltage Rating In Volts:  115.0 ac  Thread Series Designator:  | Main Contact Load Current Rating At Maximum Rated Voltage:   |
| Main Contact Maximum Voltage Rating In Volts:  115.0 ac  Thread Series Designator:  | 1.0 amperes ac resistive load  |
| 115.0 ac Thread Series Designator:  |  |
|   |  |
|   | Thread Series Designator:  |
| One single mounting facility  | Unc single mounting facility   |
| Terminal Type And Quantity:   |  |
| 4 pin all functions   |  |
| Shelf Life:   | ·  |
| N/a   |  |

## NSN 5945-00-518-7886

Electromagnetic Relay - Page 2 of 2



|   | 1  | :. | ~  | 84  |    |    |      |   |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A03300