

View Online at <https://aerobasegroup.com/nsn/5945-00-528-1920>

**Overall Length:**

5.130 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

4.312 inches single mounting facility

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.125 inches single mounting facility

**Overall Height:**

4.380 inches

**Overall Width:**

3.940 inches

**Environmental Protection:**

Hermetic and shock resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:**

0.213 inches single mounting facility and 0.228 inches single mounting facility

**Winding Quantity:**

1

**Coil Quantity:**

1

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

4 unthreaded hole single mounting facility

**Mounting Facility Pattern:**

Rectangular single mounting facility

**Nonpile-up Main Contact Arrangement:**

3 pole, single throw, normally open, double make, momentary action and 3 pole, single throw, normally closed, double break, momentary action

**Time Delay:**

0.025 seconds fixed operate time

**Nonpile-up Auxiliary Contact Arrangement:**

2 pole, double throw, one position momentary

**Auxiliary Contact Maximum Voltage Rating In Volts:**

200.0 ac and 28.0 dc

**Operating Voltage Rating And Type At Specificationified Temp:**

28.0 volts dc 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

125.0 amperes ac resistive load

**Main Contact Maximum Voltage Rating In Volts:**

200.0 ac

**Auxiliary Contact Load Current Rating At Maximum Rated Voltage:**

3.0 amperes ac resistive load and 3.0 amperes dc resistive load

**Terminal Type And Quantity:**

9 threaded stud contacts

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A03300