

View Online at <https://aerobasegroup.com/nsn/5945-00-528-1920>

Overall Length:

5.130 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.312 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.125 inches single mounting facility

Overall Height:

4.380 inches

Overall Width:

3.940 inches

Environmental Protection:

Hermetic and shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

0.213 inches single mounting facility and 0.228 inches single mounting facility

Winding Quantity:

1

Coil Quantity:

1

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

3 pole, single throw, normally open, double make, momentary action and 3 pole, single throw, normally closed, double break, momentary action

Time Delay:

0.025 seconds fixed operate time

Nonpile-up Auxiliary Contact Arrangement:

2 pole, double throw, one position momentary

Auxiliary Contact Maximum Voltage Rating In Volts:

200.0 ac and 28.0 dc

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

125.0 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

200.0 ac

Auxiliary Contact Load Current Rating At Maximum Rated Voltage:

3.0 amperes ac resistive load and 3.0 amperes dc resistive load

Terminal Type And Quantity:

9 threaded stud contacts

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A03300