## NSN 5945-00-537-4601

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-537-4601

2a single mounting facility

**Overall Length:** 

1.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.500 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.125 inches single mounting facility

**Overall Height:** 

1.000 inches

**Overall Width:** 

1.000 inches

**Environmental Protection:** 

Hermetic

Winding Quantity:

**Coil Quantity:** 

Winding Dc Resistance Rating:

1.000 kilohms single winding

**Duty Type:** 

Continuous

**Mounting Facility Type And Quantity:** 

2 threaded stud single mounting facility

**Pile-up Main Contact Form Arrangement:** 

2c

**Thread Size:** 

0.112 inches single mounting facility

**Mounting Facility Pattern:** 

In-line single mounting facility

**Operating Current Rating And Type:** 

20.0 milliamperes dc single winding

**Operating Voltage Rating And Type At Specificationified Temp:** 

20.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes dc inductive load

Main Contact Maximum Voltage Rating In Volts:

24.0 dc

**Special Features:** 

Minus 40 degrees c to plus 85 degrees c operating temp range, 1 w maximum coil dissipation

**Thread Series Designator:** 

Unc single mounting facility

## NSN 5945-00-537-4601

Electromagnetic Relay - Page 2 of 2



Fsc Application Data (non-core):	Fsc	<b>Applicat</b>	ion	Data (	non-co	re):
----------------------------------	-----	-----------------	-----	--------	--------	------

Relay armature except engine

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300