

View Online at <https://aerobasegroup.com/nsn/5945-00-539-0922>

Thread Class:

2b single mounting facility

Overall Length:

2.437 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.812 inches single mounting facility

Overall Height:

1.656 inches

Overall Width:

1.625 inches

Environmental Protection:

Shock proof

Winding Quantity:

1

Coil Quantity:

1

Winding Dc Resistance Rating:

360.0 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

2 threaded hole single mounting facility

Thread Size:

0.138 inches single mounting facility

Mounting Facility Pattern:

In-line single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Time Delay:

0.04 seconds fixed operate time

Nonpile-up Auxiliary Contact Arrangement:

2 pole, double throw, one position momentary

Auxiliary Contact Maximum Voltage Rating In Volts:

28.0 dc

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

5.0 amperes ac resistive load and 5.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac

Special Features:

Shockproof construction

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

8 pin all functions

Specification Or Standard:

Selected and tested for nuclear system selection

Reference Number Differentiating Characteristics:

As differentiated by selected and tested for nuclear system

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A03300