NSN 5945-00-539-3624

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-539-3624

| Thread Class: |
|--|
| 2a single mounting facility |
| Overall Length: |
| 3.900 inches |
| Overall Height: |
| 2.310 inches |
| Overall Width: |
| 3.000 inches |
| Environmental Protection: |
| Hermetic |
| Frequency In Hertz: |
| 60.0 |
| Winding Quantity: |
| 1 |
| Coil Quantity: |
| 1 |
| Winding Dc Resistance Rating: |
| 500.0 ohms single winding |
| Duty Type: |
| Continuous |
| Mounting Facility Type And Quantity: |
| 3 threaded stud single mounting facility |
| Thready Qty Per Inch (tpi): |
| 32 single mounting facility |
| Thread Size: |
| 0.164 inches single mounting facility |
| Mounting Facility Pattern: |
| Triangle single mounting facility |
| Nonpile-up Main Contact Arrangement: |
| 3 pole, single throw, normally open, momentary action |
| Operating Current Rating And Type: |
| 230.0 milliamperes ac single winding |
| Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: |
| 0.843 inches single mounting facility |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 115.0 volts ac 25 degrees celsius single winding |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 7.5 amperes ac resistive load |
| Main Contact Maximum Voltage Rating In Volts: |
| 440.0 ac |
| Special Features: |
| Glass insulated terminals, cadmium plated housing |

NSN 5945-00-539-3624

Electromagnetic Relay - Page 2 of 2



| | T | hr | ead | Series | Design | nator |
|--|---|----|-----|---------------|--------|-------|
|--|---|----|-----|---------------|--------|-------|

Unc single mounting facility

Terminal Type And Quantity:

8 pin all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300