# NSN 5945-00-542-0983

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-542-0983

## **Overall Length:**

1.719 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

1.406 inches single mounting facility

#### **Overall Height:**

1.520 inches

#### **Overall Width:**

0.525 inches

#### **Mounting Slot Width:**

0.150 inches single mounting facility

#### **Case Material:**

Metal

**Environmental Protection:** 

#### Hermetic

Fragility Factor:

#### Moderately rugged

Winding Quantity:

1

#### **Purpose For Which Designed:**

General

#### **Coil Quantity:**

1

#### Winding Dc Resistance Rating:

900.0 ohms single winding

#### **Duty Type:**

Continuous

#### Arc Quenching Method:

Air

## Mounting Facility Type And Quantity:

2 slotted hole single mounting facility

## Storage Type:

General purpose warehouse

#### **Cubic Measure:**

1.372 cubic inches

## Mounting Facility Pattern:

In-line single mounting facility

## Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

### Time Delay:

0.0085 seconds fixed operate and release time

## Operating Voltage Rating And Type At Specificationified Temp:

26.0 volts dc 25 degrees celsius single winding

## NSN 5945-00-542-0983

Electromagnetic Relay - Page 2 of 2



Main Contact Load Current Rating At Maximum Rated Voltage:

5.0 amperes ac resistive load and 5.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Terminal Type And Quantity:

8 pin all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300