NSN 5945-00-552-5674

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-552-5674

| Overall Length: |
|---------------------------------------------------------------------------|
| 5.375 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 4.875 inches single mounting facility |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 2.000 inches single mounting facility |
| Overall Height: |
| 2.000 inches |
| Overall Width: |
| 2.500 inches |
| Case Material: |
| Metal |
| Unthreaded Mounting Hole Diameter: |
| 0.219 inches single mounting facility |
| Fragility Factor: |
| Moderately rugged |
| Winding Quantity: |
| 2 |
| Purpose For Which Designed: |
| General |
| Coil Quantity: |
| 2 |
| Duty Type: |
| Continuous |
| Arc Quenching Method: |
| Air |
| Mounting Facility Type And Quantity: |
| 4 unthreaded hole single mounting facility |
| Storage Type: |
| General purpose warehouse |
| Cubic Measure: |
| 26.875 cubic inches |
| Mounting Facility Pattern: |
| Rectangular single mounting facility |
| Nonpile-up Main Contact Arrangement: |
| 2 pole, single throw, normally open, double make, momentary action |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 28.0 volts dc 25 degrees celsius all windings |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 10.0 amperes ac inductive load and 10.0 amperes dc inductive load |
| Main Contact Maximum Voltage Rating In Volts: |
| 115.0 ac and 28.0 dc |

NSN 5945-00-552-5674

Electromagnetic Relay - Page 2 of 2



Test Data Document:

81349-mil-r-6106 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

8 threaded stud all functions

Specification Data:

96906-ms24155 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300

Mil-std (military Standard):

Mil-r-6106 spec.