NSN 5945-00-552-7217

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-552-7217

Thread Class:
2a single mounting facility
Overall Length:
4.000 inches
Overall Height:
2.430 inches
Overall Diameter:
1.650 inches
Environmental Protection:
Hermetic
Winding Quantity:
1
Coil Quantity:
1
Winding Dc Resistance Rating:
700.0 ohms single winding
Duty Type:
Continuous
Mounting Facility Type And Quantity:
3 threaded stud single mounting facility
Pile-up Main Contact Form Arrangement:
1c
1c
1c Thready Qty Per Inch (tpi):
1c Thready Qty Per Inch (tpi): 32 single mounting facility
1c Thready Qty Per Inch (tpi): 32 single mounting facility Thread Size:
Thready Qty Per Inch (tpi): 32 single mounting facility Thread Size: 0.138 inches single mounting facility
Thready Qty Per Inch (tpi): 32 single mounting facility Thread Size: 0.138 inches single mounting facility Mounting Facility Pattern:
Thready Qty Per Inch (tpi): 32 single mounting facility Thread Size: 0.138 inches single mounting facility Mounting Facility Pattern: Ciruclar single mounting facility
Thready Qty Per Inch (tpi): 32 single mounting facility Thread Size: 0.138 inches single mounting facility Mounting Facility Pattern: Ciruclar single mounting facility Operating Current Rating And Type:
Thready Qty Per Inch (tpi): 32 single mounting facility Thread Size: 0.138 inches single mounting facility Mounting Facility Pattern: Ciruclar single mounting facility Operating Current Rating And Type: 20.0 milliamperes dc single winding
Thready Qty Per Inch (tpi): 32 single mounting facility Thread Size: 0.138 inches single mounting facility Mounting Facility Pattern: Ciruclar single mounting facility Operating Current Rating And Type: 20.0 milliamperes dc single winding Operating Voltage Rating And Type At Specificationified Temp:
Thready Qty Per Inch (tpi): 32 single mounting facility Thread Size: 0.138 inches single mounting facility Mounting Facility Pattern: Ciruclar single mounting facility Operating Current Rating And Type: 20.0 milliamperes dc single winding Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding
Thready Qty Per Inch (tpi): 32 single mounting facility Thread Size: 0.138 inches single mounting facility Mounting Facility Pattern: Ciruclar single mounting facility Operating Current Rating And Type: 20.0 milliamperes dc single winding Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage:
Thready Qty Per Inch (tpi): 32 single mounting facility Thread Size: 0.138 inches single mounting facility Mounting Facility Pattern: Ciruclar single mounting facility Operating Current Rating And Type: 20.0 milliamperes dc single winding Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 4.0 amperes ac resistive load
Thready Qty Per Inch (tpi): 32 single mounting facility Thread Size: 0.138 inches single mounting facility Mounting Facility Pattern: Ciruclar single mounting facility Operating Current Rating And Type: 20.0 milliamperes dc single winding Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 4.0 amperes ac resistive load Angle Between Adjacent Mounting Facilities:
Thready Qty Per Inch (tpi): 32 single mounting facility Thread Size: 0.138 inches single mounting facility Mounting Facility Pattern: Ciruclar single mounting facility Operating Current Rating And Type: 20.0 milliamperes dc single winding Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 4.0 amperes ac resistive load Angle Between Adjacent Mounting Facilities: 120.0 degrees single mounting facility
Thready Qty Per Inch (tpi): 32 single mounting facility Thread Size: 0.138 inches single mounting facility Mounting Facility Pattern: Ciruclar single mounting facility Operating Current Rating And Type: 20.0 milliamperes dc single winding Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 4.0 amperes ac resistive load Angle Between Adjacent Mounting Facilities: 120.0 degrees single mounting facility Main Contact Maximum Voltage Rating In Volts:
Thready Qty Per Inch (tpi): 32 single mounting facility Thread Size: 0.138 inches single mounting facility Mounting Facility Pattern: Ciruclar single mounting facility Operating Current Rating And Type: 20.0 milliamperes dc single winding Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 4.0 amperes ac resistive load Angle Between Adjacent Mounting Facilities: 120.0 degrees single mounting facility Main Contact Maximum Voltage Rating In Volts: 50.0 ac

5 pin all functions

NSN 5945-00-552-7217

Electromagnetic Relay - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300