NSN 5945-00-553-5210

Electromagnetic Relay - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5945-00-553-5210

| Overall Length: |
|--|
| 9.750 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 6.000 inches single mounting facility |
| Overall Height: |
| 6.500 inches |
| Overall Width: |
| 8.188 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.120 inches single mounting facility |
| Frequency In Hertz: |
| 60.0 |
| Winding Quantity: |
| 1 |
| Coil Quantity: |
| 1 |
| Duty Type: |
| Continuous |
| Mounting Facility Type And Quantity: |
| 3 unthreaded hole single mounting facility |
| Mounting Facility Pattern: |
| Triangle single mounting facility |
| Nonpile-up Main Contact Arrangement: |
| 3 pole, single throw, normally open, momentary action |
| Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: |
| 5.125 inches single mounting facility |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 120.0 volts ac 25 degrees celsius single winding |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 15.0 amperes ac resistive load |
| Main Contact Maximum Voltage Rating In Volts: |
| 230.0 ac |
| Terminal Type And Quantity: |
| 8 screw all functions |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A03300 |