NSN 5945-00-556-3425

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-556-3425

| Thread Class: |
|--|
| 2a single mounting facility |
| Overall Length: |
| 3.120 inches |
| Overall Height: |
| 1.780 inches |
| Overall Width: |
| 2.030 inches |
| Environmental Protection: |
| Hermetic |
| Winding Quantity: |
| 1 |
| Coil Quantity: |
| 1 |
| Winding Dc Resistance Rating: |
| 360.0 ohms single winding |
| Duty Type: |
| Continuous |
| Mounting Facility Type And Quantity: |
| 3 threaded stud single mounting facility |
| Thread Size: |
| 0.138 inches single mounting facility |
| Mounting Facility Pattern: |
| Triangle single mounting facility |
| Nonpile-up Main Contact Arrangement: |
| 2 pole, double throw, one position momentary |
| Operating Current Rating And Type: |
| 67.0 milliamperes dc single winding |
| Time Delay: |
| 0.04 seconds fixed operate time |
| Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: |
| 1.500 inches single mounting facility |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 24.0 volts dc 25 degrees celsius single winding |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 5.0 amperes ac resistive load and 1.2 amperes dc resistive load |
| Main Contact Maximum Voltage Rating In Volts: |
| 175.0 ac and 125.0 dc |
| Thread Series Designator: |
| Unc single mounting facility |
| Terminal Type And Quantity: |

8 pin all functions

NSN 5945-00-556-3425

Electromagnetic Relay - Page 2 of 2



| | Life: |
|--|-------|
| | |
| | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300