

View Online at <https://aerobasegroup.com/nsn/5945-00-557-4079>

Overall Length:

3.750 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.875 inches single mounting facility

Overall Height:

2.310 inches

Overall Width:

2.250 inches

Unthreaded Mounting Hole Diameter:

0.156 inches single mounting facility

End Application:

An/fpa-3a

Frequency In Hertz:

60.0

Winding Quantity:

1

Coil Quantity:

1

Winding Dc Resistance Rating:

235.0 ohms single winding

Duty Type:

Intermittent

Mounting Facility Type And Quantity:

3 unthreaded hole single mounting facility

Pile-up Main Contact Form Arrangement:

4c

Mounting Facility Pattern:

Triangle single mounting facility

Operating Current Rating And Type:

160.0 milliamperes ac single winding

Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

3.375 inches single mounting facility

Operating Voltage Rating And Type At Specificationified Temp:

115.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

5.0 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

120.0 ac

Terminal Type And Quantity:

2 tab, solder lug energizing element

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A03300