NSN 5945-00-565-0085

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-565-0085

view Offilite at https://aerobasegroup.com/hsh/0040-000-0000
Thread Class:
2a single mounting facility
Thread Direction:
Right-hand single mounting facility
Overall Length:
1.625 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.928 inches single mounting facility and 0.948 inches single mounting facility
Overall Height:
2.469 inches
Overall Width:
1.438 inches
Case Material:
Metal
Environmental Protection:
Hermetic
Fragility Factor:
Moderately rugged
Contact Material:
Silver
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
13.8 kilohms single winding
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
3 threaded stud single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
5.770 cubic inches
Thready Qty Per Inch (tpi):
32 single mounting facility
Thread Size:

Till cau Oize.

0.138 inches single mounting facility

NSN 5945-00-565-0085

Electromagnetic Relay - Page 2 of 2



Mounting	Facility	Pattern:
viouriting	1 acmity	i attern.

Triangle single mounting facility

Nonpile-up Main Contact Arrangement:

1 pole, double throw, one position momentary

Operating Current Rating And Type:

1.8 milliamperes dc single winding

Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

1.177 inches single mounting facility and 1.197 inches single mounting facility

Main Contact Load Current Rating At Maximum Rated Voltage:

3.0 amperes ac resistive load and 3.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 26.0 dc

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

5 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

_

Demilitarization:

No

Fiig:

A03300