

View Online at <https://aerobasegroup.com/nsn/5945-00-572-5608>

Overall Length:

2.440 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.000 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.000 inches single mounting facility

Overall Height:

2.500 inches

Overall Width:

2.440 inches

Environmental Protection:

Hermetic

Unthreaded Mounting Hole Diameter:

0.170 inches single mounting facility

Winding Quantity:

1

Coil Quantity:

1

Winding Dc Resistance Rating:

200.0 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

3 pole, single throw, normally open, momentary action

Operating Current Rating And Type:

160.0 milliamperes dc single winding

Time Delay:

0.05 seconds fixed operate time

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

50.0 amperes ac resistive load and 25.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Test Data Document:

81349-mil-r-6106 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

8 threaded stud all functions

Specification Data:

96906-ms27751 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300

Mil-std (military Standard):

Mil-prf-6106 spec.