NSN 5945-00-577-0870

Electrical Solenoid - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-577-0870

Thread Class:
2a mounting facility stud
Body Style:
Armature end actuator
Bolt Circle Diameter:
0.875 inches
Body Diameter:
1.312 inches
Body Height:
0.781 inches
Case Material:
Steel
Case Surface Treatment:
Cadmium
Environmental Protection:
Any acceptable
Maximum Operating Temp:
20.0 degrees celsius
Inclosure Type:
Fully enclosed
M
Magnetic Coil Quantity:
1
1
1 Electrical Resistance:
1 Electrical Resistance: 75.40 ohms
1 Electrical Resistance: 75.40 ohms Duty Type:
1 Electrical Resistance: 75.40 ohms Duty Type: Continuous
1 Electrical Resistance: 75.40 ohms Duty Type: Continuous Terminal Location:
1 Electrical Resistance: 75.40 ohms Duty Type: Continuous Terminal Location: Circumference
1 Electrical Resistance: 75.40 ohms Duty Type: Continuous Terminal Location: Circumference Electric Power Rating:
Electrical Resistance: 75.40 ohms Duty Type: Continuous Terminal Location: Circumference Electric Power Rating: 9.0 watts
Electrical Resistance: 75.40 ohms Duty Type: Continuous Terminal Location: Circumference Electric Power Rating: 9.0 watts Voltage Rating In Volts:
Electrical Resistance: 75.40 ohms Duty Type: Continuous Terminal Location: Circumference Electric Power Rating: 9.0 watts Voltage Rating In Volts: 28.0 dc
Electrical Resistance: 75.40 ohms Duty Type: Continuous Terminal Location: Circumference Electric Power Rating: 9.0 watts Voltage Rating In Volts: 28.0 dc Mounting Facility Type And Quantity:
Electrical Resistance: 75.40 ohms Duty Type: Continuous Terminal Location: Circumference Electric Power Rating: 9.0 watts Voltage Rating In Volts: 28.0 dc Mounting Facility Type And Quantity: 2 threaded stud
Electrical Resistance: 75.40 ohms Duty Type: Continuous Terminal Location: Circumference Electric Power Rating: 9.0 watts Voltage Rating In Volts: 28.0 dc Mounting Facility Type And Quantity: 2 threaded stud Current Rating:
Electrical Resistance: 75.40 ohms Duty Type: Continuous Terminal Location: Circumference Electric Power Rating: 9.0 watts Voltage Rating In Volts: 28.0 dc Mounting Facility Type And Quantity: 2 threaded stud Current Rating: 535.0 amperes
Electrical Resistance: 75.40 ohms Duty Type: Continuous Terminal Location: Circumference Electric Power Rating: 9.0 watts Voltage Rating In Volts: 28.0 dc Mounting Facility Type And Quantity: 2 threaded stud Current Rating: 535.0 amperes Torque Rating And Type:
Electrical Resistance: 75.40 ohms Duty Type: Continuous Terminal Location: Circumference Electric Power Rating: 9.0 watts Voltage Rating In Volts: 28.0 dc Mounting Facility Type And Quantity: 2 threaded stud Current Rating: 535.0 amperes Torque Rating And Type: 0.77 inch-pounds starting and 0.32 inch-pounds end

Plate coupling

NSN 5945-00-577-0870 Electrical Solenoid - Page 2 of 2



Plate Coupling Facility And Quantity:
1 unthreaded hole
Plate Coupling Facility Diameter:
0.125 inches
Thread Size:
0.125 inches mounting facility stud
Mounting Facility Pattern:
Two position in-line
Rotation Direction And Energizing Stroke In Angular Deg:
45.0 clockwise
Special Features:
7/32 inch lg pin mounted in hole of plate
Thread Series Designator:
Unc mounting facility stud
Terminal Type And Quantity:
2 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A134a0