

View Online at <https://aerobasegroup.com/nsn/5945-00-577-1626>

Overall Length:

4.500 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.750 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.875 inches single mounting facility

Overall Height:

2.750 inches

Overall Width:

3.250 inches

Environmental Protection:

Dustproof

Unthreaded Mounting Hole Diameter:

0.199 inches single mounting facility

Frequency In Hertz:

60.0

Winding Quantity:

1

Coil Quantity:

1

Winding Dc Resistance Rating:

64.0 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

6 unthreaded hole single mounting facility

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

1 pole, single throw, normally open, momentary action

Operating Current Rating And Type:

10.0 amperes ac single winding

Time Delay:

3.00 minutes fixed operate time

Operating Voltage Rating And Type At Specificationified Temp:

115.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

10.0 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac

Test Data Document:

81349-mil-r-2033 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

4 pin all functions

Reference Number Differentiating Characteristics:

Vlsu

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A03300