

View Online at <https://aerobasegroup.com/nsn/5945-00-577-1626>

**Overall Length:**

4.500 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.750 inches single mounting facility

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.875 inches single mounting facility

**Overall Height:**

2.750 inches

**Overall Width:**

3.250 inches

**Environmental Protection:**

Dustproof

**Unthreaded Mounting Hole Diameter:**

0.199 inches single mounting facility

**Frequency In Hertz:**

60.0

**Winding Quantity:**

1

**Coil Quantity:**

1

**Winding Dc Resistance Rating:**

64.0 ohms single winding

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

6 unthreaded hole single mounting facility

**Mounting Facility Pattern:**

Rectangular single mounting facility

**Nonpile-up Main Contact Arrangement:**

1 pole, single throw, normally open, momentary action

**Operating Current Rating And Type:**

10.0 amperes ac single winding

**Time Delay:**

3.00 minutes fixed operate time

**Operating Voltage Rating And Type At Specificationified Temp:**

115.0 volts ac 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

10.0 amperes ac resistive load

**Main Contact Maximum Voltage Rating In Volts:**

115.0 ac

**Test Data Document:**

81349-mil-r-2033 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

4 pin all functions

**Reference Number Differentiating Characteristics:**

Vlsu

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A03300