# NSN 5945-00-578-9991

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-578-9991

## **Thread Class:**

2a single mounting facility

#### **Overall Length:**

1.620 inches

# Center To Center Distance Between Mounting Facilities Parallel To Width:

0.940 inches single mounting facility

#### **Overall Height:**

2.510 inches

#### **Overall Width:**

1.410 inches

#### **Case Material:**

Metal

**Environmental Protection:** 

Hermetic

### Fragility Factor:

## Moderately rugged

**Contact Material:** 

Silver

Winding Quantity:

1

**Purpose For Which Designed:** 

General

**Coil Quantity:** 

1

#### Winding Dc Resistance Rating:

245.0 ohms single winding

**Duty Type:** 

Continuous

Arc Quenching Method:

Air

#### Mounting Facility Type And Quantity:

3 threaded stud single mounting facility

#### Storage Type:

General purpose warehouse

#### Cubic Measure:

5.733 cubic inches

### **Thread Size:**

0.138 inches single mounting facility

### Mounting Facility Pattern:

Triangle single mounting facility

### Nonpile-up Main Contact Arrangement:

1 pole, single throw, normally open, double make, momentary action

# NSN 5945-00-578-9991

Electromagnetic Relay - Page 2 of 2



98.0 milliam	peres dc single winding
Time Delay:	
-	ds fixed operate time
	enter Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle
1.190 inches	s single mounting facility
Operating V	oltage Rating And Type At Specificationified Temp:
24.0 volts dc	25 degrees celsius single winding
Main Conta	ct Load Current Rating At Maximum Rated Voltage:
60.0 ampere	s dc resistive load
Main Conta	ct Maximum Voltage Rating In Volts:
28.0 dc	
Special Fea	tures:
Four termina	als common to contact terminals
Precious Ma	aterial And Location:
Contacts silv	ver
Precious Ma	aterial:
Silver	
Thread Seri	es Designator:
Unc single m	nounting facility
Terminal Ty	pe And Quantity:
4 wire hook e	energizing element and contacts
Shelf Life:	
N/a	
Unit Of Mea	sure:
Demilitariza	tion:
No	
Fiig:	
A03300	