NSN 5945-00-583-2051

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-583-2051

Thread Class:
2a single mounting facility
Thread Direction:
Right-hand single mounting facility
Overall Length:
1.531 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.875 inches single mounting facility
Overall Height:
2.062 inches
Overall Width:
1.531 inches
Case Material:
Metal
Environmental Protection:
Hermetic
Fragility Factor:
Moderately rugged
Winding Quantity:
Wilding Quantity.
1
1
1 Purpose For Which Designed:
1 Purpose For Which Designed: General
Purpose For Which Designed: General Coil Quantity:
Purpose For Which Designed: General Coil Quantity:
Purpose For Which Designed: General Coil Quantity: 1 Duty Type:
Purpose For Which Designed: General Coil Quantity: 1 Duty Type: Continuous
Purpose For Which Designed: General Coil Quantity: 1 Duty Type: Continuous Arc Quenching Method:
Purpose For Which Designed: General Coil Quantity: 1 Duty Type: Continuous Arc Quenching Method: Air
Purpose For Which Designed: General Coil Quantity: 1 Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity:
Purpose For Which Designed: General Coil Quantity: 1 Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 3 threaded stud single mounting facility
Purpose For Which Designed: General Coil Quantity: 1 Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 3 threaded stud single mounting facility Storage Type:
Purpose For Which Designed: General Coil Quantity: 1 Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 3 threaded stud single mounting facility Storage Type: General purpose warehouse
Purpose For Which Designed: General Coil Quantity: 1 Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 3 threaded stud single mounting facility Storage Type: General purpose warehouse Cubic Measure:
Purpose For Which Designed: General Coil Quantity: 1 Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 3 threaded stud single mounting facility Storage Type: General purpose warehouse Cubic Measure: 4.833 cubic inches

0.112 inches single mounting facility

Mounting Facility Pattern:

Triangle single mounting facility

Nonpile-up Main Contact Arrangement:

6 pole, double throw, one position momentary

NSN 5945-00-583-2051

Electromagnetic Relay - Page 2 of 2



Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

1.000 inches single mounting facility

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

1.5 amperes ac motor load and 1.5 amperes dc motor load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Test Data Document:

81349-mil-r-6106 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

20 tab, solder lug all functions

Specification Data:

96906-ms25918 government standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A03300

Mil-std (military Standard):

Mil-r-6106 spec.