

View Online at <https://aerobasegroup.com/nsn/5945-00-583-5880>

**Thread Class:**

2a single mounting facility

**Overall Length:**

1.332 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.500 inches single mounting facility

**Overall Height:**

1.955 inches

**Overall Width:**

0.960 inches

**Environmental Protection:**

Corrosion resistant and hermetic

**Winding Quantity:**

1

**Coil Quantity:**

1

**Winding Dc Resistance Rating:**

252.0 ohms single winding and 308.0 ohms single winding

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

3 threaded stud single mounting facility

**Thread Qty Per Inch (tpi):**

40 single mounting facility

**Thread Size:**

0.112 inches single mounting facility

**Mounting Facility Pattern:**

Triangle single mounting facility

**Nonpile-up Main Contact Arrangement:**

3 pole, single throw, normally open, momentary action

**Nonpile-up Auxiliary Contact Arrangement:**

2 pole, single throw, normally open, momentary action

**Auxiliary Contact Maximum Voltage Rating In Volts:**

28.0 dc

**Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:**

1.000 inches single mounting facility

**Operating Voltage Rating And Type At Specificationified Temp:**

28.0 volts dc 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

1.0 amperes ac resistive load

**Main Contact Maximum Voltage Rating In Volts:**

115.0 ac

**Auxiliary Contact Load Current Rating At Maximum Rated Voltage:**

5.0 amperes dc resistive load

**Thread Series Designator:**

Unc single mounting facility

**Terminal Type And Quantity:**

12 wire hook all functions

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A03300