

View Online at <https://aerobasegroup.com/nsn/5945-00-583-5880>

Thread Class:

2a single mounting facility

Overall Length:

1.332 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.500 inches single mounting facility

Overall Height:

1.955 inches

Overall Width:

0.960 inches

Environmental Protection:

Corrosion resistant and hermetic

Winding Quantity:

1

Coil Quantity:

1

Winding Dc Resistance Rating:

252.0 ohms single winding and 308.0 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

3 threaded stud single mounting facility

Thread Qty Per Inch (tpi):

40 single mounting facility

Thread Size:

0.112 inches single mounting facility

Mounting Facility Pattern:

Triangle single mounting facility

Nonpile-up Main Contact Arrangement:

3 pole, single throw, normally open, momentary action

Nonpile-up Auxiliary Contact Arrangement:

2 pole, single throw, normally open, momentary action

Auxiliary Contact Maximum Voltage Rating In Volts:

28.0 dc

Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

1.000 inches single mounting facility

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

1.0 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac

Auxiliary Contact Load Current Rating At Maximum Rated Voltage:

5.0 amperes dc resistive load

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

12 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300