

| Electromagnetic Relay - Page 1 of 2 | AGI |
|---|-----|
| View Online at https://aerobasegroup.com/nsn/5945-00-592-1010 | |
| Overall Length: | |
| 3.500 inches | |
| Center To Center Distance Between Mounting Facilities Parallel To Length: | |
| 2.750 inches single mounting facility | |
| Overall Height: | |
| 3.500 inches | |
| Overall Width: | |
| 2.250 inches | |
| Case Material: | |
| Plastic | |
| Unthreaded Mounting Hole Diameter: | |
| 0.096 inches single mounting facility | |
| Fragility Factor: | |

Moderately rugged

Winding Quantity:

Purpose For Which Designed:

General

Coil Quantity:

Winding Dc Resistance Rating:

1.5 kilohms single winding

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

2 unthreaded hole single mounting facility

Storage Type:

General purpose warehouse

Features Provided:

Polarized

Cubic Measure:

27.563 cubic inches

Mounting Facility Pattern:

In-line single mounting facility

Nonpile-up Main Contact Arrangement:

1 pole, double throw, one position momentary

Operating Voltage Rating And Type At Specificationified Temp:

120.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

3.0 amperes ac resistive load and 3.0 amperes dc resistive load

NSN 5945-00-592-1010

Electromagnetic Relay - Page 2 of 2



Main Contact Maximum Voltage Rating In Volts:

240.0 ac and 110.0 dc

Terminal Type And Quantity:

5 tab, solder lug all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300