NSN 5945-00-592-6643

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-592-6643

Overall Length:

4.520 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.750 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.880 inches single mounting facility

Overall Height:

3.090 inches

Overall Width:

3.250 inches

Case Material:

Metal

Environmental Protection:

Hermetic

Unthreaded Mounting Hole Diameter:

0.199 inches single mounting facility

Fragility Factor:

Moderately rugged

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

6 unthreaded hole single mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

45.392 cubic inches

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Time Delay:

 $5.00\ seconds\ adjustable\ release\ time\ and\ 50.00\ seconds\ adjustable\ release\ time\ time\ adjustable\ release\ time\ adjustable\ release\ time\ adjustable\ release\ time\ adjustable\ t$

Operating Voltage Rating And Type At Specificationified Temp:

125.0 volts dc 25 degrees celsius single winding

NSN 5945-00-592-6643

Electromagnetic Relay - Page 2 of 2



Main Contact Load Current Rating At Maximum Rated Voltage:

10.0 amperes ac resistive load and 500.0 milliamperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

480.0 ac and 110.0 dc

Terminal Type And Quantity:

8 screw all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300