# NSN 5945-00-603-6473

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-603-6473

## **Overall Length:**

6.375 inches

## Center To Center Distance Between Mounting Facilities Parallel To Length:

4.000 inches single mounting facility

## Center To Center Distance Between Mounting Facilities Parallel To Width:

4.000 inches single mounting facility

#### **Overall Height:**

5.000 inches

**Overall Width:** 

4.500 inches

**Case Material:** 

Metal

**Environmental Protection:** 

Dustproof

**Unthreaded Mounting Hole Diameter:** 

0.219 inches single mounting facility

**Fragility Factor:** 

Moderately rugged

Frequency In Hertz:

60.0

Winding Quantity:

1

**Purpose For Which Designed:** 

General

**Coil Quantity:** 

1

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

143.437 cubic inches

**Mounting Facility Pattern:** 

Rectangular single mounting facility

### Nonpile-up Main Contact Arrangement:

4 pole, single throw, normally open, momentary action and 2 pole, single throw, normally closed, momentary action

## **Operating Voltage Rating And Type At Specificationified Temp:**

440.0 volts ac 25 degrees celsius single winding

## NSN 5945-00-603-6473

Electromagnetic Relay - Page 2 of 2



Main Contact Load Current Rating At Maximum Rated Voltage:

5.0 amperes ac resistive load and 10.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

440.0 ac and 230.0 dc

Terminal Type And Quantity:

14 screw all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300