NSN 5945-00-605-6613

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-605-6613

Overall Length:

6.208 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.832 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.800 inches single mounting facility

Overall Height:

2.719 inches

Overall Width:

3.800 inches

Environmental Protection:

Hermetic

Unthreaded Mounting Hole Diameter:

0.218 inches single mounting facility

Winding Quantity:

2

Coil Quantity:

2

Duty Type:

Continuous

Mounting Facility Type And Quantity:

8 unthreaded hole single mounting facility

Features Provided:

Polarized and latching contacts

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

6 pole, single throw, normally open, momentary action

Operating Current Rating And Type:

600.0 milliamperes dc all windings

Time Delay:

0.025 seconds fixed operate time

Nonpile-up Auxiliary Contact Arrangement:

2 pole, double throw, one position momentary

Auxiliary Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius all windings

Main Contact Load Current Rating At Maximum Rated Voltage:

60.0 amperes ac resistive load and 60.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

NSN 5945-00-605-6613

Electromagnetic Relay - Page 2 of 2



Terminal Type And Quantity:

22 pin all functions

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A03300