# NSN 5945-00-605-9314

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-605-9314

#### **Overall Length:**

5.370 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

2.188 inches single mounting facility

#### Center To Center Distance Between Mounting Facilities Parallel To Width:

1.688 inches single mounting facility

#### **Overall Height:**

3.810 inches

**Overall Width:** 

4.430 inches

**Unthreaded Mounting Hole Diameter:** 

0.172 inches single mounting facility

Frequency In Hertz:

60.0

#### Winding Quantity:

vviiit

## 2

Coil Quantity:

2

#### Duty Type:

Continuous

#### Arc Quenching Method:

Air

#### Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

#### **Features Provided:**

Latching contacts and polarized

#### Mounting Facility Pattern:

Rectangular single mounting facility

#### Nonpile-up Main Contact Arrangement:

1 pole, single throw, normally open, momentary action

#### **Operating Current Rating And Type:**

225.0 amperes ac all windings

#### Nonpile-up Auxiliary Contact Arrangement:

1 pole, single throw, normally open, momentary action

#### Auxiliary Contact Maximum Voltage Rating In Volts:

28.0 dc

#### Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts ac 25 degrees celsius all windings

#### Main Contact Load Current Rating At Maximum Rated Voltage:

225.0 amperes dc resistive load

#### Main Contact Maximum Voltage Rating In Volts:

28.0 dc

# NSN 5945-00-605-9314

Electromagnetic Relay - Page 2 of 2



### Terminal Type And Quantity:

6 pin all functions

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A03300